

Multi-component Analyser

MGC 16



Flow
computers

Measuring
Systems

Remote
Terminal Unit

Analysis
system

The MGC 16 is a new generation analyser for the analysis of all types of gas components.

It analyses all the required components while limiting the gas consumption to carry out the measurements. Its embedded website allows user-friendly operation without software or specific license.

Very low gas consumption

Thanks to its innovative concept with no cold spots and the measurement of all the required components in a single analyser, the MGC 16 allows an exceptionally low gas consumption of 1-2 ml / min as well as a consumption of carrier gas from 2-4 ml / min.

Scalable configuration with low maintenance

The MGC 16 offers a modular global solution for scalable on-site configuration. The MGC 16 allows maintenance at low cost (possible change of columns, TCD, injector ...). The maintenance center of the analyser is based in France.



Technical data – Analyser MGC 16

Model	MGC 16	
Applications	Pure gas, natural gas, biogas, biomethane, LNG and other fluids. Delivery station, pressure reduction station, production station, isolated post, biomethane station	
Functions	Measurement acquisition, calculation, alarm management, monitoring of analog and logic input / output status, secure recording, PLC and supervisory communication, remote and wireless server	
	Calculated values	Density, Zb, SCV, ICV, Relative density, Dewpoint, unit conversions averages
Inputs/Outputs	1 DI, 2 AO, 1 AI, 2 RJ45, 1 RS485, USB, maintenance button Other I/O possible on request, 1 DO	
	Display	Optional touch display HMI via embedded web server (unlicensed)
	Enclosure	Frame : 1 - 5 modules Dimensions : 47,5 cm (P) x 43,2 cm (L) x 44 cm (H) Weight < 20 kg
	Process gas connection	Fluid : 1/8 OD, et 1/16 OD Electrical: removable screw terminal blocks
Component	THT, Methylmercaptan, i-Propylmercaptan, t-butylmercaptan, Ethylmercaptan, n-Propylmercaptan, TBM	
	Ar, He, CH ₄ , Xe, Kr, O ₂ , N ₂ , CO, H ₂	
	C3 isomers, C4 isomers, C5 isomers	
	Ethylene, acetylene, C ₂ , C ₃ , CO ₂	
	C ₄ , C ₅ , C ₆ , C ₇ , C ₈ , C ₉ , C ₁₀ , C ₁₁ , C ₁₂	
	BTEX, methanol, ethanol, H ₂ O	
	H ₂ S-COS, NH ₃ , isopropanol, acetone, acetaldehyde, acetonitrile, diethylether, ethyl acetate, dichloromethane, 1,2 dichloromethane, chloroform, cyclohexane, 2 butanol, THF, siloxanes D3, D4, D5, D6	
Communication	2 x Ethernet TCP/IP Modbus 1 RS485 dedicated to the communication with Modbus master (SM@RT U, others)	
Pressure and sample gas consumption	0.5 to 1 bar relative. 5 ml per injection (1-2 ml/min)	
Carrier gas	He, Argon (from 2-4 ml) of minimum quality 5.5. Recommended 6.0 for low grade components. Pressure 4 bar.	
Number of streams	Up to 16 channels with MGC 16-controlled rotary valve (via USB port)	
Repeatability	< 0,1% RSD for retention times < 1% RSD on peak areas for concentrations > = 0.1% < 0,1% RSD on the SCV	
Linearity of the detector	10 ⁶	
Data storage	On RAM saved: min, max average of% gross and normalized + THT mg / Nm ³ , H ₂ O mg / Nm ³ and SCV	
	Monthly records	12 months
	Daily records	30 days
	Hourly records	7 days
	Journal	500 events, 500 metrological alarms
	Analysis	100 à 2000 analysis on time files + 3 years of chromatograms
	Hourly and daily time averages	SCV, Wobbe index, Zb, relative density, gas composition
Languages	French, English, other languages on request	
Operating conditions	Temperature	0 to 40°C
	Relative humidity	< 95% without condensation
	Column temperature programming	Column temperature: up to 250°C T° Programming : 5°C/s max according to column Resolution : 0,1°C
Power supply	Power supply 100-240 VAC, 50-60 Hz, 5 A	
Standards and recommendations used	ASTM D7833-14, ASTM D3588, GPA 2172, GPA 2145-09, ISO 6976 :2016, GPA 2261-13 Dewpoint based on the methods of ISO 18453 and IGT Bulletin #8, OILM R140	
Custody transfer approval	N° LNE-36247	
Analysis time	< 5 minutes	

Headquarters and Manufacturing facility

ZI la Limoise

36100 Issoudun FRANCE

Phone : +33 (0)2 54 03 99 49

Fax : +33 (0)2 54 21 08 90

Mail : commercial.issoudun.meci@eiffage.com

C75109-03-GB-04/23



As MecI regularly improves its products to ever better respond to evolving market and regulatory requirements, it reserves the right to change any of the specifications of these products, and this without prior notice.

en.meci.clemessy.com